

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

Claims 1-17. **(Canceled)**

18. **(Currently amended)** In a magnet valve for actuating a fuel injector, having a magnet core (2), in which a magnet coil (3) is received that surrounds a closing spring (9), which acts on a magnet armature (10), and between a face end (8) oriented toward the magnet armature (10) and the magnet armature (10), outlet openings (18, 35) **are being formed upon prior to** impact of the magnet armature (10), the improvement comprising a hydraulic damping chamber (31) defined by one face end (12) of the magnet armature (10) and by **a an armature bounce reducing** damping face (20) of non-magnetic material (16).

19. **(Previously presented)** The magnet valve of claim 18, wherein the hydraulic damping chamber (31) extends in the radial direction.

20. **(Previously presented)** The magnet valve of claim 18, wherein the hydraulic damping chamber (31) is embodied as an annular chamber.

21. **(Previously presented)** The magnet valve of claim 19, wherein the damping face (20) is embodied of non-magnetic material (16) on the second end face (5), oriented toward the magnet armature (10), of the magnet core (2).

22. **(Previously presented)** The magnet valve of claim 21, wherein the damping face (20) extends on the second face end (5) of the magnet core (2) at a constant spacing (15) parallel from the end face (12) of the magnet core (2).

23. **(Previously presented)** The magnet valve of claim 21, wherein the damping face (20) extends in the second end face (5) of the magnet core (2) at an angle (17) relative to the end face (12) of the magnet armature (10).

24. **(Previously presented)** The magnet valve of claim 21, wherein the damping face (20), on the second face end (5) of the magnet core (2), has a luglike protrusion (32) that defines the hydraulic damping chamber (31).

25. **(Previously presented)** The magnet valve of claim 18, wherein the non-magnetic material (16) is a plastic material.

26. **(Previously presented)** The magnet valve of claim 21, wherein the non-magnetic material (16) is a plastic material.

27. **(Previously presented)** The magnet valve of claim 18, wherein the non-magnetic material (16) is glued to the second end face (5) of the magnet core (2).

28. **(Previously presented)** The magnet valve of claim 21, wherein the non-magnetic material (16) is glued to the second end face (5) of the magnet core (2).

29. **(Previously presented)** The magnet valve of claim 26, wherein the non-magnetic material (16) is glued to the second end face (5) of the magnet core (2).

30. **(Previously presented)** The magnet valve of claim 18, wherein the non-magnetic material (16) is cast on the second end face (5) of the magnet core (2).

31. **(Previously presented)** The magnet valve of claim 19, wherein the damping face (20) has a first annular face portion (21) in the radial direction.

32. **(Previously presented)** The magnet valve of claim 19, wherein the damping face (20) has a second annular face portion (22) in the radial direction, below the magnet coil (3) that is let into the magnet core (2).

33. **(Previously presented)** The magnet valve of claim 31, wherein the damping face (20) has a second annular face portion (22) in the radial direction, below the magnet coil (3) that is let into the magnet core (2), and wherein between the first annular face portion (21) and the second annular face portion (22), a graduation (29, 30) is formed.

34. **(Previously presented)** The magnet valve of claim 24, wherein the luglike protrusion (32) is embodied on a third annular face portion (23) of the damping face (20).

35. **(Previously presented)** The magnet valve of claim 18, wherein the damping face (20) extends on the second end face (5) of the magnet core (2) inside a remanent air gap (13) of the magnet valve (1).

36. **(Previously presented)** The magnet valve of claim 23, wherein the damping face (20) is embodied in the second end face (5) of the magnet core (2) in inclined fashion relative to the end face (12) of the magnet armature (10) by an angle (17) such that the hydraulic damping chamber (31) opens in the radial direction.

37. **(Previously presented)** The magnet valve of claim 23, wherein the damping face (20) is oriented on the second face end (5) of the magnet core (2) relative to the end face (12) of the magnet armature (10) at an angle (17) such that the cross section of the hydraulic damping chamber (31) narrows continuously in the radial direction.